

Product Safety Datasheet

These products are classified as Articles under REACH and are not subject to the requirements for Information in the Supply Chain (Safety Data Sheets and Labels). While sensors may release hazardous substances if damaged, this is not an intended release as defined under REACH. Sensors are not classified as hazardous under the CLP.

1. Product name / chemical identification

Electrochemical sensor to detect Oxygen (O₂).

2C2	7OX	CNLL	MICROceL OX	MOX9
2FO	7OXV	CS	MOX1	SL
2FON	AO2	CY	MOX2	T7OX
4OX1	AO3	C2PN	MOX20	T7OXV
4OX2	C2	DiveceL3	MOX3	
4OXV	CN	DO2	MOX4	
5FO	CNLH	INQOX	MOX6	

Manufacturer: City Technology Ltd., Walton Rd, Portsmouth, Hampshire, England, PO6 1SZ

Telephone: +44 23 9228 8100

Fax: +44 23 9238 6611

Email: techhelp@citytech.co.uk

Website: www.citytech.com

2. Composition / information on ingredients

Electrolyte containing potassium acetate, lead, proprietary catalyst alloy electrodes, enclosed in a plastic based housing with attached metal connections. After a short period of use, lead acetate will develop inside the sensor.

3. Hazards Identification

The electrolyte and the lead inside the sensor constitute the main potential hazards, and these may become exposed should the housing be damaged.

3.1. Electrolyte (will contain lead acetate)

3.1.1. Inhalation of electrolyte:

Inhalation is not an expected hazard unless heated to high temperatures. Mist or vapour inhalation can cause irritation to the nose, throat, and upper respiratory tract.

3.1.2. Ingestion of electrolyte:

May cause irritation of the mouth, throat, and stomach.

3.1.3. Skin or eye contact of electrolyte:

May cause redness, pain, blurred vision, and eye burns.

3.1.4. Aggravation of pre-existing conditions - Electrolyte:

Persons with pre-existing skin disorders or eye problems, or impaired respiratory function may be more susceptible to the effects of the substance. Lead acetate may cause harm to the unborn child and a possible risk of impaired fertility. Danger of cumulative effects.

Product Safety Datasheet

3.2. Lead

3.2.1. Hazards - Lead:

Exposure can cause brain damage. May cause damage to blood-forming, nervous, urinary and reproductive systems. Systems of exposure include loss of appetite, metallic taste in the mouth, anxiety, constipation, nausea, pallor, excessive tiredness, weakness, insomnia, head ache, nervous irritability, muscle and joint soreness, tremors, dizziness and abdominal pain.

3.2.2. Aggravation of pre-existing conditions - Lead:

Exposure is more likely to cause a problem for those suffering from diseases of the blood-forming, nervous, urinary and reproductive systems. Exposure to lead may result in injury to a developing foetus.

4. First-Aid Measures

4.1. In case of leakage and:

4.1.1. Eye contact with electrolyte:

Irrigate thoroughly with water for at least 15 minutes. Obtain medical advice.

4.1.2. Inhalation of electrolyte:

Remove to fresh air. Obtain medical advice.

4.1.3. Skin contact with electrolyte:

Immediately flush the skin thoroughly with water for at least 15 minutes. Remove contaminated clothing and wash before re-use. Obtain medical advice if continued irritation.

4.1.4. Ingestion of electrolyte:

If swallowed DO NOT INDUCE VOMITING. Wash out mouth thoroughly with water and give plenty of water to drink. Obtain medical advice.

4.2. In case of physical damage and:

4.2.1. Eye contact with lead:

Irrigate thoroughly with water. Obtain medical advice.

4.2.2. Inhalation of lead, fumes or dust:

Remove to fresh air. Obtain medical advice.

4.2.3. Skin contact with lead:

Immediately flush the skin thoroughly with water for at least 15 minutes. Remove contaminated clothing and wash before re-use. Obtain medical advice if continued irritation.

4.2.4. Ingestion of lead:

If swallowed and individual is conscious, induce vomiting. Obtain medical attention.

5. Fire Fighting Measures

5.1. Fire:

Not considered to be a fire hazard.

5.2. Explosion:

Not considered to be an explosion hazard.

5.3. Fire extinguishing media:

Use any means suitable for extinguishing surrounding fire.

Product Safety Datasheet

6. Accidental release measures

6.1. Damage

Should any CiTiceL® be so severely damaged or tampered with that the leakage of the contents occurs then the following procedures should be adopted:

- Avoid skin contact with any lead, liquid or internal component through the use of protective gloves.
- Disconnect CiTiceL® if it is attached to any equipment.
- Use copious amounts of clean water to wash away any spilt electrolyte, particularly important in equipment because of the corrosive nature of the electrolyte.
- Observe first aid measures in case of eye contact, inhalation, skin contact or ingestion of electrolyte or lead.

7. Handling and Storage

Must not be exposed to temperatures outside the range specified on the specification sheet.

Should not be exposed to organic vapours, which may cause physical damage to the body of the sensor. Must not be stored in areas containing organic solvents or in flammable liquid stores.

8. Exposure controls / personal protection

None in normal operation

9. Physical and chemical properties

Sensor is a sealed unit

10. Stability and reactivity

N/A

11. Toxicological information

Electrolyte is corrosive to eyes, respiratory system and skin.

12. Ecological Information

Prolonged exposure in the aquatic and terrestrial environments may lead to the release of some compounds of lead, antimony and arsenic. Very toxic to aquatic organisms.

13. Disposal Considerations

Contains toxic compounds irrespective of physical condition. Should be disposed of according to local waste management requirements and environmental legislation.

Should not be burnt since they may evolve toxic fumes.

14. Transport Regulations

City Technology's electrochemical sensors are classified as "batteries wet non-spillable" (UN2800). They are transported as per IATA PI 872 and 49CFR 173.159a, and need no special packaging, labels etc. as they are not restricted as per IATA Special Provision A67.

Product Safety Datasheet

15. Regulatory information

Hazard Statements

H360Df	May damage the unborn child. Suspected of damaging fertility.
H373	May cause damage to organs through prolonged or repeated exposure.
H410	Very toxic to aquatic life with long lasting effects.

Precautionary statement

P201	Obtain special instructions before use.
P273	Avoid release to the environment.
P308 + P313	If exposed or concerned: Get medical advice/ attention.
P501	Dispose of contents/ container to an approved waste disposal plant.